## **Patent Abstracts of Japan**

**PUBLICATION NUMBER** 

06093534

**PUBLICATION DATE** 

05-04-94

APPLICATION DATE

10-09-92

APPLICATION NUMBER

04242279

APPLICANT: TOYOTA AUTOM LOOM WORKS LTD;

INVENTOR:

SHIRAKI MASAO;


INT.CL.

D03D 47/30

TITLE

: APPARATUS FOR CONTROLLING

WEFT-INSERTION IN JET LOOM



ABSTRACT :

PURPOSE: To surely introduce a weft into a holding pipe and keep the weft tension to a proper level by stopping an auxiliary nozzle at the side of weft insertion terminal and actuating a stretch nozzle when the tip of the weft is estimated to come in the acting range of the stretch nozzle.

CONSTITUTION: A weft Y is inserted by the ejecting action of a weft-insertion main nozzle 4 and auxiliary nozzle groups 5-8 of a jet loom. The arrival time of the flying weft Y is detected by a detector 16 placed at a prescribed position in the weaving width. The arrival time of the tip end of the weft Y at the ejection action region of a stretch nozzle 10 placed at the side of weft insertion terminal is estimated by a control computer C based on the above detection result. At the same time, the computer C controls the ejection pressure wave form of the auxiliary nozzle 8 of the side of weft insertion terminal and the stretch nozzle 10, stops the ejection from the auxiliary nozzle 8 at the estimated time, starts the ejection of the stretch nozzle 10 and surely guides the tip end of the weft Y into a holding pipe 11.

COPYRIGHT: (C)1994,JPO&Japio